

Name: Pro-Tek 36
Revision Date: 7/23/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

PRO-TEK 36

NEAT RUST PREVENTIVE OIL

DESCRIPTION

Pro-Tek 36 is an oil bases, multi-purpose rust preventive designed for use in environments where high humidity protection is desired. When applied, this formulation will leave a uniform thin, oily protective film that effectively suppresses fingerprints. Pro-Tek 36 is ideal for use when metal has been exposed to water such as machining and grinding coolants or washed parts. Pro-Tek 36 is commonly used when parts are manually inspected or packaged and where ease of removal is needed on both ferrous and non-ferrous metals.

PROPERTIES

Appearance:	Clear brown liquid
Film Type:	Thin oily film
Dry Time @20°C:	N/A
Odor:	Petroleum
Film Thickness:	0.8-1.2 Micron
Density lbs/gal:	7.4
Indoor Protection:	Up to 24 months
Outdoor Protection:	Up to 6 months (covered)
Flash Point:	335°F
Water Displacing:	Yes
Paintable/Weldable:	No

FEATURES & BENEFITS

- High flash point reduces need for special precautions
- Does not contain chlorinated solvents
- Effectively penetrates cracks and crevices
- Indoor protection for all ferrous and non-ferrous parts
- Resists acidic atmospheric conditions
- Fingerprint suppressant

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.

APPLICATION

Apply product as is by brush, dip, spray or immersion to all surfaces needing protection. Allow to air dry. Drying time is dependent on temperature, relative humidity and air circulation. Remove product by wiping off with cloth or cleaner.