

Technical Data Sheet

Solutions Through Innovative Technology

Name: Val-Sol Cutting & Tapping Fluid Revision Date: 7/11/2018 - R1

ValCool, LLC 5230 Brittmoore Rd Houston, TX 77041

VAL-SOL CUTTING & TAPPING FLUID

AEROSOL CUTTING OIL

DESCRIPTION

Val-Sol Cutting & Tapping Fluid allows tools to run cooler, thereby extending tool life and increasing tool performance. Works well on both ferrous and non-ferrous metals. Excellent foaming action penetrates deep into the cut to extend tap life and promote a superior finish.

DIRECTIONS FOR USE

Shake can vigorously before use. Clean surface thoroughly. Keep can 6 to 8 inches away from surface and apply evenly at the point of cut. Thin coats are preferable. Reapply if needed.

FEATURES & BENEFITS

- Excellent cooling and lubricating properties
- Clings to the tool
- · Provides superior finish
- · Does not contain chlorinated solvents

PROPERTIES

Appearance: Amber Spray Form: Liquid

Vapor Density: Heavier than air Evaporation Rate: Slower than ether

Odor: Odor

Flammability: Level 1 Aerosol

Can Size: 20 oz. Net Weight: 16 oz.

APPLICATION

BoringSawingTappingMillingDrillingGrinding

• Reaming • Thread Cutting

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.

